

PROFESSIONAL  
LIGHTING  
FOR THE  
PERFORMING ARTS

Short form catalogue 2020



## Fresnel

Luminaires with Fresnel lens, adjustable yoke and adjustable optical zoom. Recommended for soft and even lighting. Available with motorized yokes with DMX control or pole operated yokes.

### FN LED 50

Power	50W
LED	White (3000K, 4000K, 5600K)
Control	- DMX-RDM - Local
Version	12°-76° (2,5kg - 27x16x25cm)

### FN LED 50 RGBW

Power	50W
LED	RGBW
Control	- DMX-RDM - Local
Version	13°-50° (2,5kg - 27x16x25cm)



### FN LED C100

Power	100W
LED	White (3000K, 4000K, 5600K)
Control	- DMX-RDM - Local
Version	12°-75° (3,5kg - 29x22x31cm)



### FN HY LED 200

Power	200W
LED	White (3000K, 4000, 5600K)
Control	- DMX-RDM - Local
Versions	14°-81°

### FN HY LED 200 Tunable

Power	200W
LED	White (2700K-6500K)
Control	- DMX-RDM - Local
Versions	13°-50°

### FN HY LED 200 RGBW

Power	200W
LED	RGBW
Control	- DMX-RDM - Local
Versions	13°-50°



### FN HY LED 200 6C

Power	200W
LED	RGB+AMBER+CYAN+LIME
Control	- DMX-RDM - Local
Versions	13°-50°



### FN HY LED 300

Power	300W
LED	White (3200K, 5600K)
Control	- DMX-RDM - Local
Version	09°-45°

### FN HY LED 300 Tunable

Power	300W
LED	White (2700K-6500K)
Control	- DMX-RDM - Local
Version	09°-45°

### FN HY LED 300 RGBW

Power	300W
LED	RGBW
Control	- DMX-RDM - Local
Version	12°-45°



### FN HY LED 300 6C

Power	300W
LED	RGB+AMBER+CYAN+LIME
Control	- DMX-RDM - Local
Version	12°-45°



### FN LED 450

Power	450W
LED	White (3200K, 5600K)
Control	- DMX-RDM - Local
Version	12°-58° (14kg - 55x30x53cm)

### FN LED 450 Tunable

Power	450W
LED	Tunable White (2700K-6500K)
Control	- DMX-RDM - Local
Version	12°-58° (14kg - 55x30x53cm)

### FN LED 450 RGBW

Power	450W
LED	RGBW
Control	- DMX-RDM - Local
Version	12°-58° (14kg - 55x30x53cm)



### FN LED 450 6C

Power	450W
LED	RGB+AMBER+CYAN+LIME
Control	- DMX-RDM - Local
Version	12°-58° (14kg - 55x30x53cm)



### MI FN NO

Source	Halogen
Power	300W (GY 9,5)
Version	07°-53° (1,3kg - 11x13x17cm)

### COM 05 F

Source	Halogen
Power	300/500/650W (GY 9,5)
Version	07°-62° (3kg - 15x15x25cm)

### COM 12 F

Source	Halogen
Power	1000/1200W (GX 9,5)
Version	07°-53° (5,4kg - 20x20x30cm)

### COM 25 F

Source	Halogen
Power	2000/2500W (G 22)
Version	07°-65° (10,8kg - 27x29x41cm)

## Plano-Convex

Fixtures with prism-convex lens, adjustable yoke and adjustable optical zoom. Recommended for soft and accent lighting. Available with motorized yokes with DMX control or pole operated yokes.

Architectural Series

<b>PC LED 50</b>	
Power	50W
LED	White (3000K, 4000K, 5600K)
Control	- DMX-RDM - Local
Version	08°-80° (3kg - 27x16x29cm)



<b>PC LED C100</b>	
Power	100W
LED	White (3000K, 4000K, 5600K)
Control	- DMX-RDM - Local
Version	15°-75° (3,5kg - 29x22x31cm)



Hyperion Series

<b>PC HY LED 200</b>	
Power	200W
LED	White (3000K, 4000, 5600K)
Control	- DMX-RDM - Local
Version	16°-87°

<b>PC HY LED 200 Tunable</b>	
Power	200W
LED	White (2700K-6500K)
Control	- DMX-RDM - Local
Version	15°-50°

<b>PC HY LED 200 RGBW</b>	
Power	200W
LED	RGBW
Control	- DMX-RDM - Local
Version	15°-50°

<b>PC HY LED 200 6C</b>	
Power	200W
LED	RGB+AMBER+CYAN+LIME
Control	- DMX-RDM - Local
Version	15°-50°

<b>PC HY LED 300</b>	
Power	300W
LED	White (3200K, 5600K)
Control	- DMX-RDM - Local
Version	06°-45°

<b>PC HY LED 300 Tunable</b>	
Power	300W
LED	White (2700K-6500K)
Control	- DMX-RDM - Local
Version	06°-45°

<b>PC HY LED 300 RGBW</b>	
Power	300W
LED	RGBW
Control	- DMX-RDM - Local
Version	08°-45°

<b>PC HY LED 300 6C</b>	
Power	300W
LED	RGB+AMBER+CYAN+LIME
Control	- DMX-RDM - Local
Version	08°-45°

450 Series

<b>PC LED 450</b>	
Power	450W
LED	White (3200K, 5600K)
Control	- DMX-RDM - Local
Version	09°-70° (16kg - 55x30x58cm)

<b>PC LED 450 Tunable</b>	
Power	450W
LED	Tunable White (2700K-6500K)
Control	- DMX-RDM - Local
Version	09°-70° (16kg - 55x30x58cm)

<b>PC LED 450 RGBW</b>	
Power	450W
LED	RGBW
Control	- DMX-RDM - Local
Version	09°-70° (16kg - 55x30x58cm)

<b>PC LED 450 6C</b>	
Power	450W
LED	RGB+AMBER+CYAN+LIME
Control	- DMX-RDM - Local
Version	09°-70° (16kg - 55x30x58cm)

Conventional Line

<b>MI PC NO</b>	
Source	Halogen
Power	300W (GY 9,5)
Version	07°-53° (1,6kg - 11x13x22cm)

<b>COM 05 PC</b>	
Source	Halogen
Power	300/500/650W (GY 9,5)
Version	04°-56° (3,7kg - 15x15x30cm)

<b>COM 12 PC</b>	
Source	Halogen
Power	1000/1200W (GX 9,5)
Version	04°-63° (6,8kg - 20x20x40cm)

<b>COM 25 PC</b>	
Source	Halogen
Power	2000/2500W (G 22)
Version	04°-66° (13,7kg - 27x29x53cm)

## Profile

Luminaires with adjustable shutters, adjustable yoke, adjustable optical zoom and focus. Recommended for accent and precise lighting, as well as for images projection (gobos). Available with motorized yokes with DMX control or pole operated yokes.

### PR LED 50

Power	50W
LED	White (3000K, 4000K, 5600K)
Control	- DMX-RDM - Local
Version	20°-40° (4,1kg - 37x37x43cm)

### PR LED 50 RGBW

Power	50W
LED	RGBW
Control	- DMX-RDM - Local
Version	20°-40° (4,1kg - 37x37x43cm)



### PR LED 100

Power	100W
LED	White (3000K, 4000K, 5600K)
Control	- DMX-RDM - Local
Versions	20°-38° (6kg - 40x34x54cm) 35°-50° (6kg - 40x34x45cm)

### PR HY LED 200

Power	200W
LED	White (3000K, 4000, 5600K)
Control	- DMX-RDM - Local
Versions	15°-30° 25°-50°

### PR HY LED 200 Tunable

Power	200W
LED	White (2700K-6500K)
Control	- DMX-RDM - Local
Versions	15°-30° 25°-50°

### PR HY LED 200 RGBW

Power	200W
LED	RGBW
Control	- DMX-RDM - Local
Versions	15°-30° 25°-50°



### PR HY LED 200 6C

Power	200W
LED	RGB+AMBER+CYAN+LIME
Control	- DMX-RDM - Local
Versions	15°-30° 25°-50°



### PR HY LED 300

Power	300W
LED	White (3200K, 5600K)
Control	- DMX-RDM - Local
Versions	15°-30° 25°-50°

### PR HY LED 300 Tunable

Power	300W
LED	White (2700K-6500K)
Control	- DMX-RDM - Local
Versions	15°-30° 25°-50°

### PR HY LED 300 RGBW

Power	300W
LED	RGBW
Control	- DMX-RDM - Local
Versions	15°-30° 25°-50°



### PR HY LED 300 6C

Power	300W
LED	RGB+AMBER+CYAN+LIME
Control	- DMX-RDM - Local
Versions	15°-30° 25°-50°



### PR LED 450

Power	450W
LED	White (3200K, 5600K)
Control	- DMX-RDM - Local
Versions	08°-19° (13,5kg - 55x34x87cm) 14°-30° (13,5kg - 55x34x87cm) 24°-44° (13kg - 55x34x72cm)

### PR LED 450 Tunable

Power	450W
LED	White (2700K-5600K)
Control	- DMX-RDM - Local
Versions	08°-19° (13,5kg - 55x34x87cm) 14°-30° (13,5kg - 55x34x87cm) 24°-44° (13kg - 55x34x72cm)

### PR LED 450 RGBW

Power	450W
LED	RGBW
Control	- DMX-RDM - Local
Versions	08°-19° (13,5kg - 55x34x87cm) 14°-30° (13,5kg - 55x34x87cm) 24°-44° (13kg - 55x34x72cm)



### PR LED 450 6C

Power	450W
LED	RGB+AMBER+CYAN+LIME
Control	- DMX-RDM - Local
Versions	08°-19° (13,5kg - 55x34x87cm) 14°-30° (13,5kg - 55x34x87cm) 24°-44° (13kg - 55x34x72cm)



### MI PR ZS NO

Source	Halogen
Power	300W (GY 9,5)
Versions	20°-40° (1,3kg - 11x13x17cm)

### COM 05 ZS/ZW

Source	Halogen
Power	300/500/650W (GY 9,5)
Versions	14°-33° (4,8kg - 15x15x49cm) 23°-40° (4,5kg - 15x15x40cm)

### COM 12 ZS/ZW

Source	Halogen
Power	1000/1200W (GX 9,5)
Versions	13°-35° (9,8kg - 20x20x72cm) 24°-50° (9,1kg - 20x20x57cm)

### COM 25 ZM/ZW

Source	Halogen
Power	2000/2500W (G 22)
Versions	09°-25° (25,1kg - 27x29x90cm) 17°-36° (21,3kg - 27x29x79cm)

## Followspot

Fixtures with manual focusing, adjustable yoke on stand, adjustable optical zoom and focusing. Colour changer (manual and/or DMX) not included. Recommended for accent and long distance lighting, with direct control from the operator.



**VD LED 250**

Power	250W
LED	White (3200K, 5600K)
Control	- DMX-RDM - Local
Version	08°-19° (17kg - 47x34x97cm)



**VD LED 250 RGBW**

Power	250W
LED	RGBW
Control	- DMX-RDM - Local
Version	08°-19° (17kg - 47x34x97cm)



**VD LED 450**

Power	450W
LED	White (3200K, 5600K)
Control	- DMX-RDM - Local
Version	08°-19° (22kg - 45x35x105cm)



**VD LED 450 RGBW**

Power	450W
LED	RGBW
Control	- DMX-RDM - Local
Version	08°-19° (22kg - 45x35x105cm)



450 Series

Source	Discharge
Power	1200W / MSR (GY 22)
Standard	Cold Restrike version, Iris diaphragm with black out, shaping shutters and slots for B size gobo holder
Distance	20-40 m
Version	07°-18° (18,8kg - 20x20x112cm)

Source	Discharge
Power	1200W / MSR (G 38)
Standard	Hot Restrike version, Iris diaphragm with black out, shaping shutters and slots for B size gobo holder
Distance	20-40 m
Version	07°-18° (18,8kg - 20x20x112cm)



**VD 25 H**

Source	Halogen
Power	2000/2500W (G 22)
Standard	Iris diaphragm with black out, shaping shutters and slots for A size gobo holder
Distance	15-25 m
Version	07°-16° (27kg - 27x29x115cm)



**VD 25 M HR**

Source	Discharge
Power	2500W / MSR (G 38)
Standard	Hot Restrike version, Iris diaphragm with black out, shaping shutters and slots for B size gobo holder
Distance	30-100 m
Version	05°-13° (51kg - 27x29x163cm)

Conventional Line

## Floodlight

### Asymmetric

Asymmetric cyclorama powered by LED source in RGBW. Thanks to its sophisticated specifically designed optical system, it allows to illuminate in an absolutely even way an area of over 40 sqm when positioned at a distance from the backdrop of only 1,5m.

#### CYC LED 300 RGBW



Power	300W
LED	RGBW
Control	- DMX-RDM - Local



#### DOM 1000

Source	Halogen
Power	625/1000/1250W (R7s)
Version	3,8kg - 29x28x21cm



## Downlight

Recessed LED luminaires with high-efficiency white chip. High quality polycarbonated aluminate optics.

#### HAL LED 55

Power	50W (no fan)
LED	White (3000K, 4000K, 5600K)
Control	- DALI - Local - DMX-RDM (opt.)
Versions	29° (0,75kg - 16x16x14cm) 46° (0,75kg - 16x16x14cm) 72° (0,75kg - 16x16x14cm)

#### HAL LED 90

Power	90W (no fan)
LED	White (3000K, 4000K, 5600K)
Control	- Local - DMX-RDM
Versions	29° (0,75kg - 16x16x14cm) 46° (0,75kg - 16x16x14cm) 72° (0,75kg - 16x16x14cm)



## Blacklight

Fixtures with adjustable yoke and optical system for a parallel and concentrated beam. Recommended for effect lighting.

#### W 400

Source	black light bulb 400W (E40)
Version	5,6kg - 32x32x43cm



## Pinspot

### FLUM

Micro LED fixture with variable power made of copper body with anodized aluminum base, rotation system and accessories. Internal wiring. High performing optics. Constant current power supply.

FLUM LED 3	
Power	3W (12V)
LED	White (3000K, 4000K)
Control	- DALI - Local - DMX-RDM (opt.)
Versions	06° (0,1kg - 6x5x4cm) 12° (0,1kg - 6x5x4cm) 22° (0,1kg - 6x5x4cm) 46° (0,1kg - 6x5x4cm)



Architectural Series

### LUCCIOLA

Architectural pinspot for AR-111 halogen or LED lamps.

LU LED (LED only)		SUPERLUT (for halo and no-dimmable LED)	
Power	max 40W (12V), R-111	max 75W (12V), R-111	
Lamp	not included	not included	
Control	- Local - or DMX-RDM - or DALI		
Versions	09° (1,3kg - 18x16x22cm) 24° (1,3kg - 18x16x22cm) 40° (1,3kg - 18x16x22cm)	09° (1,5kg - 18x16x22cm) 24° (1,5kg - 18x16x22cm) 40° (1,5kg - 18x16x22cm)	



## Pole Operated system

Pole Operated yokes: modular system of yokes with 2 o 3 functions (tilt, pan and focus) with safet clutch to protect gear box and to allow hand focusing



## ARC system

Automated Remote Control: motorised DMX modular yokes for high precision 16 bit focusing for tilt, pan, beam adjustment. Thanks to the modular structure it accepts all LED and Conventional Spotlight fixtures and most of the luminaires commercially available on the market.





**SPOTLIGHT sc**  
[www.spotlight.it](http://www.spotlight.it)

Operational Headquarters  
Via Sardegna, 3 - 20098 - S. Giuliano Milanese (MI) - Italia  
Quality System ISO 9001:2015

Registered Office  
Via Martino Anzi 8, 22100 Como (CO) - Italia  
VAT: IT03859900130