

Hyperion Series

200W Profile

(ver. 2021/05)



SOURCE

- 200W LED ARRAY
- Source life expectancy: > 50.000 h
- Note: for Luminous flux and Colour rendering refer to the table at the end of this document

SOFTWARE FUNCTIONS

- ESD: 8 or 16bit extra soft dimming
- 3 selectable dimmer curves
- Adjustable delay in turning on and off
- PWM LED 500Hz-20KHz
- Amber shift (6C)
- ± Green (6C)
- Color boost (6C, RGBW, TW)
- Calibration function (6C, RGBW, TW)
- Service channel
- Stand-alone
- Master Slave
- Hour-counter on single LED
- Storage and factory recovery
- Upgradable Firmware via DMX/USB tool
- Advanced remote settings for all parameters via DMX

CONTROL

- Protocols: DMX512, RDM
- Local potentiometer
- Reversible graphics display with standby-shutdown function

	DMX Channels
WHITE	1 / 2 / 3 ch
TW	2 / 5 / 9 ch
RGBW	3 / 6 / 7 / 16 ch
6C	3 / 6 / 7 / 8 / 9 / 21 ch

THERMAL MANAGEMENT

- Wide ventilation slots for better LED cooling with selectable fan speed in: "standard", "silent" and "auto" or DMX regulated
- High efficiency heat pipe cooling system
- No heat load from LED engine towards electronic and vice-versa avoiding the risk of failure due to overheating
- Ta max 40°C

OPTICS

- High-quality glass lens optics – AR coating
- Focus: manual
- Gobo size: B
- Additional fixed optics: 5° / 10° / 14° / 19° / 26° / 36° / 50° / 70° / 90°
- Note: for Beam angles refer to the table at the end of this document

PRESETS

- 45-GEL FILTER (6C, RGBW)
- CCT 2700-8000K (6C, RGBW, TW)
- 10 CUSTOM PRESETS (6C, RGBW, TW)

HOUSING

- Highly resistant body in extruded aluminum and techno-polymer body
- Finishing: Black
- IP 20

ELECTRICAL

- Power supply: 100-240 V – 50/60 Hz
- Power consumption 200 W
- PF>0.94/230VAC PF>0.98/115VAC at full load

CONNECTION

- Power connector: Chassis PowerCON TRUE1 In/Out
- Additional cable: 2m H05RN-F cable with powerCON TRUE1 female cable connector
- DMX: XLR 5-pole In/Out panel connectors

OPTIONS

- Pole Operated Yokes
- ARC Motorized Yokes DMX 512
- Market-standard fixed optics adaptor



COMPLIANCE

- CE
- EN 60598-1; EN 60598-2-17
- SSL Licensing Program
- Manufactured in Italy with Quality System ISO 9001:2015

DIMENSIONS

ZW	10.9 Kg	640*380*335 mm
ZS	11.5 Kg	760*380*335 mm

Hyperion Series

200W Profile

(ver. 2021/05)



DMX chart

	WHITE			TUNABLE WHITE		
	1CH	2CH	3CH	EASY	SPLIT	FULL
	8 BIT	8 BIT	16 BIT	8 BIT	8 BIT	16 BIT
1 ch	DIMMER	DIMMER	DIMMER	DIMMER	DIMMER	DIMMER
2 ch		STROBO	DIMMER FINE	CCT	WW	DIMMER FINE
3 ch			STROBO		CW	CCT
4 ch					STROBO	WW +/-
5 ch					SERVICE	CW +/-
6 ch						DELAY
7 ch						FAN
8 ch						STROBO
9 ch						SERVICE

	RGBW				
	EASY	HSI	CMY	RGBW	FULL
	8 BIT	8 BIT	8 BIT	8 BIT	16 BIT
1 ch	DIMMER	DIMMER	DIMMER	DIMMER	DIMMER
2 ch	CCT	HUE	CYAN	RED	DIMMER FINE
3 ch	COLOUR PRESET	HUE FINE	MAGENTA	GREEN	RED
4 ch		SATURATION	YELLOW	BLUE	RED FINE
5 ch		STROBO	STROBO	WHITE	GREEN
6 ch		SERVICE	SERVICE	STROBO	GREEN FINE
7 ch				SERVICE	BLUE
8 ch					BLUE FINE
9 ch					WHITE
10 ch					WHITE FINE
11 ch					CCT
12 ch					COLOUR PRESET
13 ch					DELAY
14 ch					FAN
15 ch					STROBO
16 ch					SERVICE

	RGBACL						
	EASY	CMY	RGB	HSI	RGBACL	THEATER	FULL
	8 BIT	8 BIT	8 BIT	8 BIT	8 BIT	16 BIT	16 BIT
1 ch	DIMMER	DIMMER	DIMMER	DIMMER	DIMMER	DIMMER	DIMMER
2 ch	CCT	CYAN	RED	HUE	RED	DIMMER FINE	DIMMER FINE
3 ch	COLOUR PRESET	MAGENTA	GREEN	HUE FINE	GREEN	CCT	RED
4 ch		YELLOW	BLUE	SATURATION	BLUE	+/- GREEN	RED FINE
5 ch		STROBO	STROBO	CCT	AMBER	DELAY	GREEN
6 ch		SERVICE	SERVICE	STROBO	CYAN	FAN	GREEN FINE
7 ch				SERVICE	LIME	STROBO	BLUE
8 ch					STROBO	SERVICE	BLUE FINE
9 ch					SERVICE		AMBER
10 ch							AMBER FINE
11 ch							CYAN
12 ch							CYAN FINE
13 ch							LIME
14 ch							LIME FINE
15 ch							COLOUR PRESET
16 ch							CCT
17 ch							+/- GREEN
18 ch							DELAY
19 ch							FAN
20 ch							STROBO
21 ch							SERVICE

Hyperion Series

200W Profile

(ver. 2021/05)



Model	Type	CT	(measure at)	CRI	TLCI	TM-30	Lumen	Beam	Lux	∅ Beam	Lux	∅ Beam	Lux	∅ Beam	Lux	∅ Beam	Lux	∅ Beam
PR HY LED 200 ZS	WW	3000K	3000K	97	97	94	3.471	15°	6.550	1,0	2.911	1,6	1.638	2,1	1.048	2,6	728	3,1
								30°	2.295	2,1	1.020	3,2	574	4,3	367	5,3	255	6,4
	NW	4000K	4000K				3.665	15°	6.917	1,0	3.074	1,6	1.729	2,1	1.107	2,6	769	3,1
								30°	2.424	2,1	1.077	3,2	606	4,3	388	5,3	269	6,4
	CW	5600K	5600K				4.276	15°	8.070	1,0	3.587	1,6	2.017	2,1	1.291	2,6	897	3,1
								30°	2.827	2,1	1.257	3,2	707	4,3	452	5,3	314	6,4
	TW	2700-6500K	4000K	3.874	95	92	93	15°	6.997	1,0	3.110	1,6	1.749	2,1	1.120	2,6	777	3,1
								30°	2.072	2,1	921	3,2	518	4,3	332	5,3	230	6,4
	RGBW	2700-8000K	Full Ch	2.944	85	90	90	15°	5.318	1,0	2.363	1,6	1.329	2,1	851	2,6	591	3,1
								30°	1.575	2,1	700	3,2	394	4,3	252	5,3	175	6,4
	6C	2700-8000K	Full Ch	3.099	94	92	94	15°	5.598	1,0	2.488	1,6	1.399	2,1	896	2,6	622	3,1
								30°	1.658	2,1	737	3,2	414	4,3	265	5,3	184	6,4
									4 m		6 m		8 m		10 m		12 m	

Model	Type	CT	(measure at)	CRI	TLCI	TM-30	Lumen	Beam	Lux	∅ Beam	Lux	∅ Beam	Lux	∅ Beam	Lux	∅ Beam	Lux	∅ Beam
PR HY LED 200 ZW	WW	3000K	3000K	97	97	94	3.647	25°	3.900	1,8	1.733	2,6	975	3,5	624	4,4	433	5,3
								50°	1.358	3,7	603	5,6	339	7,4	217	9,3	151	11,1
	NW	4000K	4000K				3.851	25°	4.119	1,8	1.830	2,6	1.030	3,5	659	4,4	458	5,3
								50°	1.434	3,7	637	5,6	358	7,4	229	9,3	159	11,1
	CW	5600K	5600K				4.493	25°	4.805	1,8	2.135	2,6	1.201	3,5	769	4,4	534	5,3
								50°	1.672	3,7	743	5,6	418	7,4	268	9,3	186	11,1
	TW	2700-6500K	4000K	4.233	95	92	93	25°	4.176	1,8	1.856	2,6	1.044	3,5	668	4,4	464	5,3
								50°	1.320	3,7	586	5,6	330	7,4	211	9,3	147	11,1
	RGBW	2700-8000K	Full Ch	3.093	85	90	90	25°	3.052	1,8	1.356	2,6	763	3,5	488	4,4	339	5,3
								50°	964	3,7	429	5,6	241	7,4	154	9,3	107	11,1
	6C	2700-8000K	Full Ch	3.256	94	92	94	25°	3.213	1,8	1.428	2,6	803	3,5	514	4,4	357	5,3
								50°	1.015	3,7	451	5,6	254	7,4	162	9,3	113	11,1
									4 m		6 m		8 m		10 m		12 m	