

PC LED 50 WW DMX

Luminaire: PC, LED, 50W, WW
zoom 08°-80°, 3000K, DMX control



Type

Green line

Family

PC

Source

LED Warm White

Power

50W

Control

DMX-RDM

Manuale

Colour temperature

Cri

> 90

Connectors

Cable without plug

Voltage

90-260V, 50-60Hz

Product sizes

3Kg

Pack sizes

215mm x 475mm x 200mm

3.4Kg

0.02m³

User manual

Available on website

Technical features

- Aluminum housing for high heat dissipation by natural ventilation
- Adjustable forced ventilation
- Filter frame lockable top cover
- Yoke with clutch-locking system
- Adjustable yoke for fixture balancing


Functional features

- LED temperature range control to guarantee the best performances
- Constant colour temperature during the whole dimming curve
- Remote controllable functions via DMX-RDM


Green line advantages

- No dangerous UV or IR rays for the safe lighting of the people and objects
- No radioactive or mercury-based components
- Nearly 75% saving on mains power consumption if compared to an equally-performing conventional fixture
- Reduced installation and cabling costs thanks to the In&Out chain connection system both for power mains and DMX/DALI data control
- Savings on running costs thanks to the extended lifespan of the LED source compared to the periodical replacement of conventional bulbs
- Savings on the air-con setup and supply, thanks to the lower heat emission of the fixtures
- No maintenance costs for the replacement of colour filters due to overheating and damage

Sizes (in mm)



Light output diagram



Accessories

BASE-Q122-AS

FUNE

HC/075

MINI GAC

PL 4 MINI

TC MINI

TRK ROS-7705-B

TRK ROS-7705-N

SQUARE BASE SET

Acc: Safety net with spring hook

Acc: Half swivel coupler 75kg max

Acc: Hook clamp for 30mm tube

Acc: 4-door bamdoors

Acc: Colour frame

Acc: Mechanical track adaptor -W

Acc: Mechanical track adaptor -B