

PC LED C100 CW DMX

Luminaire: PC, LED, 100W, CW
zoom 08°-87°, 5600K, DMX control



Type

Green line

Family

PC

Source

LED Cool White

Power

100W

Control

DMX-RDM

Manuale

Colour temperature

5600K

Cri

>90

Connectors

Powercon® h&Out

Voltage

90-260V, 50-60Hz

Product sizes

3.5Kg

Pack sizes

190mm x 235mm x 386mm

3.8Kg

0.017m³

DWG

Available on website

User manual

Available on website

Technical features

- Aluminum housing for high heat dissipation by natural ventilation
- Adjustable forced ventilation
- Filter frame lockable top cover
- Yoke with clutch-locking system
- Adjustable yoke for fixture balancing
- PO version on request, with 3-way pole operation for tilt, pan and focus
- ARC version on request, with 3-way DMX control of tilt, pan and focus


Functional features

- LED temperature range control to guarantee the best performances
- Constant colour temperature during the whole dimming curve
- Remote controllable functions via DMX-RDM


Green line advantages

- No dangerous UV or IR rays for the safe lighting of the people and objects
- No radioactive or mercury-based components
- Nearly 75% saving on mains power consumption if compared to an equally-performing conventional fixture
- Reduced installation and cabling costs thanks to the h&Out chain connection system both for power mains and DMX/DALI data control
- Savings on running costs thanks to the extended lifespan of the LED source compared to the periodical replacement of conventional bulbs
- Savings on the air-con setup and supply, thanks to the lower heat emission of the fixtures
- No maintenance costs for the replacement of colour filters due to overheating and damage

Sizes (in mm)



Light output diagram



Accessories

CP 81	Lamp: halogen 300W 230V 3200K GY9.5
CP 82	Lamp: halogen 500W 230V 3200K GY9.5
CP 89	Lamp: halogen 650W 230V 3200K GY9.5
DOU-00001513	
FUNE	Acc: Safety net with spring hook
GAC	Acc: Hook clamp for 40/50mm tube
HC/075	Acc: Half swivel coupler 7.5kg max
M 38	Lamp: halogen 300W 230V 2950K GY9.5
M 40	Lamp: halogen 500W 230V 2950K GY9.5
PL 4 U05	Acc: 4-door barndoors
PO/2 SP05	Yoke: Pole Operated for Pan-Tilt
PO/3 SP05	Yoke: Pole Operated for Pan-Tilt-Focus
R S05	Acc: Safety net
T 18	Lamp: halogen 500W 230V 3050K GY9.5
T 26	Lamp: halogen 650W 230V 3050K GY9.5
TC S05	Acc: Colour frame


SPOTLIGHT
professional lighting for the performing arts